

**DETECTOR DE FUM ESSER IQ8Quad 802382,
cu semnalizare alarma, cu izolator -2 bucati**



Specificatii tehnice:

Curent de repaus:	50 μ A (19 VDC) / aproximativ 280 μ A (acumulator FACP)
Aria de monitorizare:	>110 m ²
Grad de protectie:	minim IP40
Material:	ABS
Culoare:	alb, RAL 9010
Alimentare:	intre 9 si 42 VDC
Temperatura de functionare:	intre -20°C si +50°C
Umiditate:	max 95%

Garantie: 24 luni

Buton avertizare incendiu adresabil - 1 bucata

Specificatii tehnice:

Alimentare	16-28VDC
Consum static	<0.5mA
Consum alarmare	<1.0mA
Temperatură	10-55°C
Umiditate	<95%
Dimensiuni	100mm x 100mm x 43mm
Greutate	110g

Garantie: 24 luni

Acumulator plumb 12V/18A – 1 bucata

Specificatii tehnice:

Tip	Acumulator AGM VRLA Acumulator Plumb Acid AGM
Capacitate (Ah)	18 Ah
Output Voltage (V)	12 V
Tensiune intrare (V)	12 V
Tensiune de alimentare (V)	12 V
Dimensiuni (W x H x D mm)	77 X 167 X 181
Greutate (Kg)	5.15
Altele	12 V / 18 Ah

Borne tip saibă pt surub

Garantie: 24 luni